



**R-410A AND NEW R-32 MODELS**



### Air Handlers

An air handler regulates the circulation of the heated or cooled indoor air to help reach the temperature that you have set on your thermostat or control system. Depending on the design of your home, an air handler may be a principal indoor component of your split heat pump system.

When properly matched with your heat pump, the indoor air handler is designed to circulate conditioned air through your home's ductwork efficiently. Make sure that your system is performing to its optimum level with our Amana brand air handlers.

Air Handlers									
MODELS	NEW R-32 MODELS						AMVE MULTI-POSITION	MBVB MODULAR BLOWER	MBVK MODULAR BLOWER
	230V AHVE / 230V AHVE*13 MULTI-POSITION	115V AHVE / 115V AHVE*03 MULTI-POSITION	AMVT / AMVT*13 MULTI-POSITION	AMST / AMST*13 MULTI-POSITION	AWST / AWST*13 WALL-MOUNT	ACSF / ACST*13 CEILING MOUNT			
Refrigerant Compatible	R-410A / R-32 (230V AHVE*13 is R-32)	R-410A / R-32 (115V AHVE*03 is R-32)	R-410A / R-32 (AMVT*13 is R-32)	R-410A / R-32 (AMST*13 is R-32)	R-410A / R-32 (AWST*13 is R-32)	R-410A / R-32 (ACST*13 is R-32)	R-410A	R-410A	R-410A
Furnace Integration Kit required for R-32 compatibility	N/A	N/A	N/A	N/A	N/A	N/A	N/A	•	•
10-Year Parts Limited Warranty*	•	•	•	•	•	•	•	•	•
ComfortBridge™ Compatible	**ComfortNet™ Only	**ComfortNet™ Only	•	N/A	N/A	N/A	•	•	**ComfortNet™ Only
ALL-ALUMINUM Evaporator Coil	•	•	•	•	•	•	•	N/A	N/A
Factory-Mounted TXVs	Factory-mounted EEV	Factory-mounted EEV	•	•	•	Factory-mounted TXV included on the ACST*13	Factory-mounted EEV	N/A	N/A
Tonnage	2 to 5 Ton	2 to 5 Ton	2 to 5 Ton	2 to 5 Ton	1 ½ to 3 Ton	1 ½ to 2 ½ Ton	2 to 5 Ton	1 ½ to 5 Ton	2 to 5 Ton
Motor Type	Variable-Speed ECM	Variable-Speed ECM	Variable-Speed ECM	9 TAP ECM	Multi-Speed ECM	Direct-Drive, Multi-Speed	Variable-Speed ECM	Variable-Speed ECM	Variable-Speed ECM
UL 60335 2-40 Compliant	•	•	•	•	•	•	•	•	•

\* Complete warranty details available from your local dealer or at www.amana-hac.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in Florida, California, or Quebec. The duration of warranty coverages in Florida and Texas differs in some cases.

## Additional information

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.



### WARNINGS:

It is recommended to use best practices and always adhere to safety protocols before, during, and when working with any refrigerants.

### DO NOT MIX REFRIGERANTS

- Per current US EPA SNAP approvals, A2L refrigerants can only be used in new equipment and CANNOT be used to retrofit a different refrigerant into an existing system. Always use the same refrigerant marked on the nameplate.
- Codes are rapidly changing and allowing A2L refrigerants throughout North America. Check with your local Daikin Comfort Technologies Distributor for latest product availability information.



A DAIKIN BRAND

Our continuing commitment to quality products may mean a change in specifications without notice.

© 2025 DAIKIN COMFORT TECHNOLOGIES NORTH AMERICA, INC. · Houston, Texas · USA · [www.amana-hac.com](http://www.amana-hac.com)

Amana® is a registered trademark of Maytag Corporation or its related companies and is used under license. All rights reserved.

PF-A\_AH\_03-25