

Project Name:	Approval:
Location:	Date:
Engineer:	Construction:
Submitted to:	Unit #:
Submitted by:	Drawing #:
Reference:	

MODEL COMPATIBILITY:

Compatible with Light Commercial unit models: DFC, DRC, DP14CM, DFG, DRG, DP14GM, DFH, DRH, DP14HM, DX13SA, DX14XA, DZ14SA, DZ14XA

SPECIFICATIONS:

Model	D4271C/D4272C
Description	Premium Series Thermostat
Power	24VAC
Dimensions	5.6" x 4.2" x 1.1"
Heating Stage	4
Cooling Stage	2

PRODUCT IMAGE:



FEATURES:

- Adjustable backlight intensity/disable
- 10 character 16 segment status line display, adjustable scrolling
- Fahrenheit or Celsius Display
- Installer test-mode to exercise equipment during startup
- Manual or auto changeover
- Schedule formats: 0, 1, (5/1/1), 7 day
- 4 stage heat, 2 stage cool
- Configurable setpoints of additional stage control
- Adjustable stage timers/deadbands
- Adjustable thermal-off fan delay
- Security Levels (set point limiting, etc.)
- Configurable dry contact input: condensate, occupied, equipment fault, holiday, door switch
- Service Filter reminder
- UV lamp replacement reminder
- Aux heat indicator
- Holiday mode
- Comfort recovery
- Override Counter
- Keypad lock
- Daily runtime trend
- Optional Wi-Fi Module available for Skyport Cloud Services and configurator app
- Alexa and Google Assistant compatible

D4272C ONLY:

- Programmable output (time/temp/aux/economizer/error)
- Integrated Humidity sensor
- Overcool to dehumidify
- Humidifier Pad service reminder
- Outdoor/Remote sensor ready
- Temperature averaging
- Hi/Lo outdoor temperature tracking

Daikin North America LLC, 19001 Kermier Rd, Waller TX, 77484

www.daikinac.com www.daikincity.com

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Project Name:	Approval:
Location:	Date:
Engineer:	Construction:
Submitted to:	Unit #:
Submitted by:	Drawing #:
Reference:	

WIRING INSTRUCTION:

Connector	Function	Connector	Function
R	24VAC	C	24VAC common
G	Fan relay	REMOTE/OUTDOOR*	Remote/Outdoor Sensor
W1/O/B	1 st stage heat circuit; reversing valve	AUX	Aux Output
W2	2 nd stage heat circuit	HUM	Humidifier
W3	3 rd stage heat circuit	DEHUM	Dehumidifier
Y1	1 st stage cooling compressor relay	DRY CONTACT	Dry Contact Switch
Y2	2 nd stage cooling compressor relay		

*D4272C only

ACCESSORIES:

Available accessories:

	PSPAC-LR – Lockring		PSPAC-PWF – Wi-Fi Module
	PSPAC-WP –Wall Plate		PSPAC-WS – Wired Sensor (D4272C only)

DOCUMENTATION:

Documentation available on www.daikincity.com, www.daikinac.com and/or www.daikinthermostats.com:

- Submittal
- Installation and Operation Manual
- Product flyer