

Submittal Data Sheet Electric Heat Kit for FXTQ HKS(X)C03/05/06/08/10/15/19/20/25

DESCRIPTION

The electrical heat kit mounts directly inside FXTQ to provide auxiliary heating or to be used as alternate heat.

FEATURES

- Allows for easy addition axillary heat to supplement heating capabilities without any major equipment changes
- Sequencers for better temperature control
- Multiple branch circuit capability
- Completely assembled and tested
- Control circuitry arranged to readily permit staging
- Factory-installed circuit breakers available on specific models
- Fuse link secondary high-temperature limit control
- Plug-in wiring harness for ease of installation into air handler
- Rust-resistant nickel chromium heat elements

Specification													
Model No.	Heater Capacity	Voltage	With Circuit	Unit Compatibility FXTQ_TAVJUA / FXTQ_TAVJUD									
			Breaker?	9	12	18	24	30	36	42	48	54	60
HKSX03XC	3 kW	208/240V	no	✓	✓	✓	✓	✓	✓	-	-	-	-
HKSC05XC	5 kW	208/240V	yes	\checkmark	\checkmark	✓	\checkmark	\checkmark	\checkmark	\checkmark	✓	\checkmark	\checkmark
HKSX05XC	5 kW	208/240V	no	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
HKSX06XC	6 kW	208/240V	no	-	1	1	✓	✓	1	✓	✓	✓	✓
HKSX08XC	8 kW	208/240V	no	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
HKSX10XC	10 kW	208/240V	no	-	✓	✓	✓	✓	✓	✓	✓	✓	✓
HKSC15XA	15 kW	208V	yes	-	-	-	-	-	-	✓	✓	1	✓
HKSC15XB	15 kW	240V	yes	-	-	-	-	-	-	✓	✓	1	✓
HKSC19CA	19 kW	208V	yes	-	-	-	-	-	-	✓	✓	-	-
HKSC19CB	19 kW	240V	yes	-	-	-	-	-	-	✓	✓	-	-
HKSC20DA	20 kW	208V	yes	-	-	-	-	-	-	-	-	✓	✓
HKSC20DB	20 kW	240V	yes	-	-	-	-	-	-	-	-	1	✓
HKSC25DC	25 kW	208/240V	yes	-	-	-	-	-	-	-	-	✓	✓

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston TX, 77056 www.daikinac.com www.daikincomfort.com

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations).

